



Windshield Repair Systems

Tri Glass Pit Buffer

Part Number: 116

Specifically formulated to remove fine hairline scratches from all aircraft, boat, motorcycle, automotive, industrial and residential clear plastic and glass windows.

Directions: Shake well. Apply liberal amount on a soft terrycloth and rub thoroughly into surface. Product will dry white. Remove with separate soft terrycloth.

Caution: Contains petroleum distillates. If swallowed, **do not induce vomiting.** Call physician immediately.

I. HAZARDOUS INGREDIENTS

Hazardous Components	Concentration %	C.A.S. Number	OSHA PEL	TLV
Light Distillate	15-20	64742-14-9	No limit	No limit
Natural Diatomaceous Earth	4-8	61790-53-2	10 mg/m3	No limit
Glycerine	2-5	56-81-5	10mg/m3	10mg/m3
Hydrotreated Distillate	5-10	64742-46-7	No limit	No Limit
Conditioners	3-8	PROPRIATARY	No limit	No limit

II. PHYSICAL PROPERTIES

Vapor Pressure: <10 mm Hg at 70°C	Specific Gravity: 1.00	Vapor Density (air=1): >1
Boiling / Melting point: > 390° F	% VOC's at 70° F: 14% max	Evaporation Rate: <1
Solubility in Water: Appreciable		pH: 5.50
Appearance and Odor: Thick yellow-green liquid, sweet hydrocarbon odor		

III. FLAMMABILITY AND EXPLOSIVE PROPERTIES

Flash point: > 200°F (PMCC-ASTM D93-90)	LEL: N/A	UEL: N/A
Recommended Extinguishing Agents: Dry chemical, water, foam or CO2.		
Special Fire Fighting Procedures or Hazards: Self-contained breathing apparatus		

IV. REACTIVITY DATA

Stability: Stable	Incompatibility: Strong oxidizers, acids
Hazardous Polymerization: Will not occur.	Hazardous Decomposition: Carbon monoxide and carbon dioxide.
Conditions to Avoid: None	

V. SAFE HANDLING PROCEDURES

In Case of Spill or Leak: Contain and absorb. May be contained in metal, plastic or glass.		
Waste Disposal: Sanitary landfills for absorbent materials, or as required by Federal, State and local regulations.		
Caution in Handling and Storing: Keep away from extreme heat.		
Respiratory Protection: None required for normal use.		
Ventilation: Local exhaust: Adequate	Mechanical: None	Special: None
Gloves (neoprene): For sensitive skin		
Eye Protection: Where splashing occurs		
Other Protective Equipment: None		

VI. HEALTH HAZARD DATA

Potential Routes of Entry: Skin, eyes, inhalation and ingestion
Symptoms of Overexposure: Possible skin and eye irritation on contact. Prolonged or intentional exposure to high concentrations may cause respiratory track irritation. May be harmful if swallowed. Can cause intestinal distress
Carcinogenicity: None
Conditions Aggravated by Overexposure: Dermatitis
Emergency First Aid: Wash eyes with copious amount of water. If irritation persists, get medical attention. Thoroughly was skin with soap and water. If swallowed give glasses of water, but do not induce vomiting. GET MEDICAL ATTENTION if breathing becomes difficult.

10/03/02

Tri Glass Pit Buffer MSDS