

**Product Trade Name: SMART BLEND ATF PROTECTANT #4001
(RED BOTTLE)**



Material Safety Data Sheet

Section 1 PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: SMART BLEND ATF PROTECTANT #4001 (RED BOTTLE)

Company Identification

Life Automotive Products, Inc.
500 Industrial Park Drive
Selmer, TN 38375-3276
United States of America

Emergency Response

North America: CHEMTREC (800) 424-9300 after 5:00pm CST
Or (703) 527-3887

Health Emergency

USA: (800) 264-6457 or (731) 645-4972

Product Information

MSDS Requests: (800) 264-6457 or (731) 645-4972
Technical Information: (800) 264-6457 or (731)645-4972
General Information: vswedley@spectrumcorporation.com

Product Family **Petroleum Lubricating Oil**
CAS Number **Mixture**

Note: Petroleum lubricating oils with a flashpoint above 200°F, are not regulated by D.O.T standards.

Section 2 HAZARDS IDENTIFICATION

IMMEDIATE HEALTH EFFECTS

Inhalation: Breathing mists and vapors may cause slight respiratory tract irritation. Breathing vapors from product when heated to temperatures above 150°F which then may contain Hydrogen Sulfide, can also cause headaches, dizziness, nausea, coughing, bronchial irritation and dryness, and in sufficient quantities, unconsciousness.

**Product Trade Name: SMART BLEND ATF PROTECTANT #4001
(RED BOTTLE)**

Eye Contact: Components of this product have been determined to be irritating and corrosive to eyes

Skin Contact: Components of this product have been determined to be irritating and corrosive to skin.

Ingestion: Minor components (<5%) of this product have been determined to be mildly to moderately toxic (LD50: <1/5g/kg).

TLV: This product does not contain any components which have recognized exposure limits. However a TLV of 5.0 mg/cubic meter for oil mist.

Chronic Effects: This product may contain ingredients that are listed as potential carcinogens in N.T.P. Annual Report on Carcinogens, I.A.R.C. Monographs, or by O.S.H.A. HCS (g) (2) (vii).

Section 3 COMPOSITION/INFORMATION ON INGREDIENTS

| COMPONENTS | CAS Number | Concentration (%) |
|---------------------------------|--------------|-------------------|
| Antiwear Additive | Confidential | <2 |
| Alkyl acid phosphate | 68307-94-8 | <2 |
| Amines, Soya alkyl, ethoxylated | 61791-240 | 10-15 |
| Zinc dialkyl dithiophosphate | 68649-42-3 | <0.5 |
| Branched Alkanes | 68649-11-6 | 10-15 |
| Benzotriazole derivative | Confidential | <0.5 |
| Polyalphaolefins | Mixture | 30-40 |
| Petroleum distillates | 64742-54-7 | 30-40 |
| Viscosity Modifier (PPD) | Mixture | 3-5 |
| C.I. Slvent Red 164 Red Dye* | See Below | <0.05 |

*2-Naphthalenol (Phenylazo) Phenyl Azo Alkyl Derivatives. TSCA Accession #35371

Note that the chemical identity of some or all of the above components is considered confidential business information and is being withheld as permitted by 29CFR 1910.1200 and various State Right-To-Know Laws.

Section 4 FIRST AID MEASURES

Skin: Remove material from skin by patting or blotting with a clean cloth. Wash exposed areas with soap and water for at least 15 minutes. Seek medical attention immediately. Do not reuse contaminated clothing until

**Product Trade Name: SMART BLEND ATF PROTECTANT #4001
(RED BOTTLE)**

laundered. Discard all contaminated leather goods.

Eye: DO NOT RUB EYES. Immediately wash eyes with large amounts of water for at least 15 minutes. Remove contact lenses before washing. Seek medical attention immediately.

Inhalation: If symptoms of Hydrogen Sulfide exposure are indicated, remove individual(s) to fresh air and administer oxygen. Seek medical attention immediately.

Ingestion: DO NOT INDUCE VOMITING. If vomiting occurs spontaneously, watch for signs of aspiration. Seek medical attention immediately.

Section 5 FIRE FIGHTING MEASURES

PROTECTION OF FIRE FIGHTERS:

Fire Fighting Instructions:

For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self contained breathing apparatus.

Extinguishing Media: Use water spray, dry chemical, foam or carbon dioxide. Water or foam may cause frothing. Water spray may be used to flush spills away from exposures. Use supplied-air breathing equipment for enclosed or confined spaces, or as otherwise needed.

Special Firefighting Procedures: Cool exposed containers with water spray. Avoid breathing gasses, vapor, fumes, or decomposition of products. Self-contained breathing equipment chemical resistant clothing recommended.

Unusual Fire and Explosion Hazards: Pressure increase in over heated closed containers. Cool containers with water spray. product of combustion includes fumes & CO₂

Section 6 ACCIDENTAL RELEASE MEASURES

Spill Procedures: Remove ignition sources. Recover Liquid. Add absorbent to spill area. Ventilate confined spaces. Advise authorities if product enters sewers, etc.

Waste Disposal: Assure conformity with applicable disposal regulations. Dispose of absorbed material at approved waste site.

Precautionary Measures:

Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Wash thoroughly after handling.

General Handling Information:

Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

**Product Trade Name: SMART BLEND ATF PROTECTANT #4001
(RED BOTTLE)**

Section 7 HANDLING AND STORAGE

General Storage Information:

Keep container closed when not in use. Do not store with strong oxidizing agents. Do not store at elevated temperatures.

Container Warnings:

Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

Section 8 EXPOSURE CONTROLS/ PERSONAL PROTECTION

| COMPONENTS | Regulatory Agency | Exposure Limit |
|---------------------------------|-------------------|--------------------|
| Antiwear Additive | OSHA | 5mg/m ³ |
| Alkyl acid phosphate | OSHA | 5mg/m ³ |
| Amines, Soya alkyl, ethoxylated | OSHA | 5mg/m ³ |
| Zinc dialkyl dithiophosphate | OSHA | 5mg/m ³ |
| Branched Alkanes | OSHA | 5mg/m ³ |
| Benzotriazole derivative | | 5mg/m ³ |
| Polyalphaolefins | OSHA | 5mg/m ³ |
| Petroleum distillates | OSHA | 5mg/m ³ |
| Viscosity Modifier (PPD) | OSHA | 5mg/m ³ |
| C.I. Slvent Red 164 Red Dye* | OSHA | 5mg/m ³ |

- Ventilation Procedure:** Ventilate as needed to comply with exposure limit.
- Gloves Protection:** Use impervious gloves to avoid repeated/prolonged skin contact.
- Eye Protection:** Use goggles/face shield to avoid eye contact.
- Work/Hygienic Practices:** If clothing becomes contaminated, change to fresh clean clothing. Do not wear until thoroughly laundered.

Section 9 PHYSICAL AND CHEMICAL PROPERTIES

**Product Trade Name: SMART BLEND ATF PROTECTANT #4001
(RED BOTTLE)**

| | |
|---------------------------------------|---------------------------------|
| Boiling Point | Not Determined |
| Vapor Pressure (mm Hg) | Less than 0.01 mm Hg @ 20°C |
| Vapor Density (air=1) | Greater than 5 |
| Solubility in Water | Negligible; less than 0.1% |
| Appearance and Odor | Red /Mild, bland petroleum odor |
| Specific Gravity (H ₂ O=1) | 0.8581 @ 60°F |
| Evaporation Rate | Not Determined |
| Viscosity @ 100 | 7.2 cSt (typical) |
| Flash Point | 270°F COC |

Section 10 STABILITY AND REACTIVITY

| | |
|-------------------------------|---|
| Stability: | Stable |
| Incompatibility: | Avoid strong oxidants |
| Polymerization: | Will not occur |
| Thermal Decomposition: | Oxides of Carbon, Nitrogen & Sulfur, & Phosphorus, Methacrylate Monomers. Under certain conditions, Ammonia & Hydrogen Sulfide. |

Section 11 TOXICOLOGY INFORMATION

Distillates (petroleum), hydrotreated light

ORAL (LD50): Acute: >5000 mg/kg [Rat].

DERMAL (LD50): Acute: >2000 mg/kg [Rabbit].

Studies on laboratory animals have associated similar materials with eye and respiratory tract irritation. Repeated exposure to elevated concentrations of hydrocarbon solvents can produce a variety of transient CNS effects (e.g., dizziness, headache, narcosis, etc). Studies on laboratory animals have shown similar materials to cause skin irritation after repeated or prolonged contact. Repeated direct application of similar materials to the skin can produce defatting dermatitis and kidney damage in laboratory animals. The most common effects observed in repeated dose animal studies with mineral spirits are kidney changes that are consistent with an alpha 2u-globulin- mediated process that is not regarded as relevant to humans. Certain studies have reported effects in the liver as well as hematological or urine chemistry changes. In general, these effects have not to been shown to be dose-related.

Highly-refined petroleum lubricant oils:

ORAL (LD50): Acute: >5000 mg/kg [Rat].

DERMAL (LD50): Acute: >2000 mg/kg [Rabbit].

Mineral oil mists derived from highly refined oils are reported to have low acute and sub-acute toxicities in animals. Effects from single and short-term repeated exposures to high concentrations of mineral oil mists well above applicable workplace exposure levels include lung inflammatory reaction, lipoid granuloma formation and lipoid pneumonia. In acute and sub-acute studies involving exposures to lower concentrations of mineral oil mists at or near current work place exposure levels produced no significant toxicological effects. In long term studies (up to two years) no carcinogenic effects have been reported in any animal species tested.

**Product Trade Name: SMART BLEND ATF PROTECTANT #4001
(RED BOTTLE)**

Section 12 ECOLOGICAL INFORMATION

Ecotoxicity

An environmental fate analysis is not available for this specific product. Plants and animals may experience harmful or fatal effects when coated with petroleum products. Petroleum-based (mineral) lubricating oils normally will float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway may be sufficient to cause a fish kill or create an anaerobic environment.

Environmental Fate

Analysis for ecological effects has not been conducted on this product. However, if spilled, this product and any contaminated soil or water may be harmful to human, animal, and aquatic life. Also, the coating action associated with petroleum and petroleum products can be harmful or fatal to aquatic life and waterfowl.

Section 13 DISPOSAL CONSIDERATIONS

Waste Disposal: Assure conformity with applicable disposal regulations.
Dispose of absorbed material at approved waste site.

Section 14 TRANSPORTATION INFORMATION

The shipping description below may not represent requirements for all modes of transportation, shipping methods or locations outside of the United States.

US DOT Status Not Regulated

Section 15 REGULATORY INFORMATION

TSCA Inventory This product and/or its components are listed on the Toxic Substances Control Act (TSCA) inventory.

| SARA 313 Toxic Chemical Notification and Release Reporting | CAS Number | Wt % | Component Name |
|---|------------|------|-----------------------------|
| | 68649-42-3 | <0.5 | Zinc dialkyldithiophosphate |

Clean Water Act (CWA) This material is classified as an oil under Section 311 of the Clean Water Act (CWA) and the Oil Pollution Act of 1990 (OPA). Discharges or spills which produce a visible sheen on waters of the United States, their adjoining shorelines, or into conduits leading to surface waters must be reported to the EPA's National Response Center at (800) 424-8802.

**Product Trade Name: SMART BLEND ATF PROTECTANT #4001
(RED BOTTLE)**

**California
Proposition 65**

This product contains the following chemical(s) known to the state of California to cause cancer and/or birth defects based on maximum impurity levels of components: 0.00006% Toluene
CAS no 108-88-3

**New Jersey
Right-to-Know Label**

Petroleum Oil
<0.5% Zinc dialkyldithiophosphate

Section 16 OTHER INFORMATION

The data presented herein is based upon tests and information, which we believe to be reliable. However, users should make their own investigations to determine the suitability of the information for their particular purpose.