



MATERIAL SAFETY DATA SHEET

SECTION I

PRODUCT NAME OR NUMBER (as it appears on label) QMI Synthetic Blend Limited Slip Differential Supplement (LSD 100)		DATE 04/11/2007
MANUFACTURER'S NAME QMI		EMERGENCY TELEPHONE #: QMI: (800) 255-8138 CHEM-TEL: (800) 255-3924
ADDRESS (Number, Street, City, State and Zip Code) 3606 Craftsman Blvd., Lakeland, FL 33803 USA		
HAZARDOUS MATERIAL DESCRIPTION, PROPER SHIPPING NAME, HAZARD CLASS, HAZARD ID NO. None		
ADDITIONAL HAZARD CLASSES (as applicable) In accordance with OSHA 29 CFR 1910-1200	CHEMICAL FAMILY Petroleum	FORMULA Proprietary

SECTION II (list ingredients)

CAS REGISTRY NO.	%W	%V	CHEMICAL NAME(S)	LISTED AS A CARCINOGEN
61791-24-0	< 50		Ethoxylated Alkyl Amines	Not Listed
68649-42-3	< .5%		Zinc Alkyl Dithiophosphate	Not Listed
Proprietary	< .1%		Confidential Accession	Not Listed
64741-88-4	< 2%		Mineral Oil	Not Listed
647412-53-6	< 5%		Mineral Oil	Not Listed
64742-58-1	20-40%		Mineral Oil	Not Listed
68649-11-6	20-40%		1-Decene, Dimer Hydrogenated	Not Listed

SECTION III - PHYSICAL DATA

BOILING POINT > 500°F	SPECIFIC GRAVITY 0.89	
VAPOR DENSITY (AIR=1) > 5	EVAPORATION RATE N/A	PERCENT SOLD BY WEIGHT (%) N/A
SOLUBILITY IN WATER Insoluble		
APPEARANCE AND ODOR amber liquid mild odor	IS MATERIAL:	<u>LIQUID</u> SOLID GAS PASTE POWDER

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

NFPA (30) Class IIIB HMIS Ratings: Health - 1, Flammability - 1, Reactivity - 0		
FLASH POINT > 260°F	METHOD USED COC	EXTINGUISHING MEDIA Carbon Dioxide Foam and Dry chemical and water fog.
SPECIAL FIRE FIGHTING PROCEDURES Water spray may be used to keep exposed containers cool. (Enclosed fires) Self contained breathing apparatus must be used.		UNUSUAL FIRE AND EXPLOSION HAZARDS None

