



Revision Number: 004.1

Issue date: 04/15/2011

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	LOCTITE® Chisel® Paint Stripper	IDH number:	135544
Product type:	Cleaner	Item number:	79040
		Region:	United States
Company address:	Contact information:		
Henkel Corporation	Telephone: 860.571.5100		
One Henkel Way	MEDICAL EMERGENCY Phone: Poison Control Center		
Rocky Hill, Connecticut 06067	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkelna.com		

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Physical state:	Aerosol, Liquid	HEALTH:	*3
Color:	Gray, to, Off white	FLAMMABILITY:	4
Odor:	Sharp, Solvent	PHYSICAL HAZARD:	1
		Personal Protection:	See MSDS Section 8

DANGER: EXTREMELY FLAMMABLE LIQUID AND VAPOR.
 CONTENTS UNDER PRESSURE.
 MAY CAUSE EYE AND SKIN BURNS.
 MAY BE HARMFUL OR FATAL IF INHALED, ABSORBED THROUGH SKIN OR SWALLOWED.
 MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
 POSSIBLE CANCER HAZARD.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation:	Inhalation of vapor or aerosol may cause severe irritation to nose, throat and lungs.
Skin contact:	May cause irritation due to defatting of the skin. Prolonged contact can cause reddening, swelling, rash, scaling, blistering and in some cases, skin sensitization.
Eye contact:	Mists, vapors or liquid may cause severe irritation or burns.
Ingestion:	Not expected under normal conditions of use. May be harmful or fatal if swallowed.

Existing conditions aggravated by exposure: Not available

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Methylene chloride	75-09-2	60 - 100
Petroleum gases, liquified, sweetened	68476-86-8	10 - 30
Methanol	67-56-1	5 - 10
Propylene oxide	75-56-9	0.1 - 1

4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If symptoms persist, seek medical advice.
Skin contact:	Rinse with running water and soap. If symptoms develop and persist, get medical attention.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Seek medical advice.
Ingestion:	Do not induce vomiting. Call a physician immediately.

5. FIRE FIGHTING MEASURES

Flash point:	< 5 °C (< 41°F)
Autoignition temperature:	Not available
Flammable/Explosive limits - lower:	Not available
Flammable/Explosive limits - upper:	Not available
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Firefighters should wear self-contained breathing apparatus. Water may be ineffective, but may be used to cool exposed containers to prevent pressure build-up and possible auto-ignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable.
Unusual fire or explosion hazards:	Vapours may accumulate in low or confined areas, travel considerable distance to source of ignition, and flash back. Aerosol cans may rupture in heat or fire conditions.
Hazardous combustion products:	Irritating organic vapours. Phosgene. Hydrogen chloride. Oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow to enter the ground / soil.
Clean-up methods:	Remove all sources of ignition. Spilled liquid is combustible and can be ignited by heat, flames, sparks, or other sources of ignition. Store in a closed container until ready for disposal. Soak up with inert absorbent. Scrape up spilled material and place in a closed container for disposal. For small spills wipe up with paper towel and place in container for disposal.

7. HANDLING AND STORAGE

Handling:	Use only in well-ventilated areas. Avoid contact with eyes, skin and clothing. Avoid breathing mists or aerosols of this product.
Storage:	Store in a cool, dry, well-ventilated area. Store in original container until ready to use.

Shelf Life Statement: Not available

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Methylene chloride	50 ppm TWA	12.5 ppm OSHA ACT (SKIN) 29 CFR 1910.1052 25 ppm TWA 125 ppm STEL	None	None
Petroleum gases, liquified, sweetened	None	None	None	None
Methanol	200 ppm TWA (SKIN) 250 ppm STEL	200 ppm (260 mg/m ³) TWA	None	None
Propylene oxide	2 ppm TWA (Sensitiser.)	100 ppm (240 mg/m ³) TWA	None	None

Engineering controls:	Use only in area provided with appropriate exhaust ventilation.
Respiratory protection:	Use NIOSH approved respirator if there is potential to exceed exposure limit(s). Use only in well-ventilated areas.
Eye/face protection:	Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.
Skin protection:	Chemical resistant, impermeable gloves. Silver Shield gloves. Viton gloves. Polyvinyl alcohol gloves. 4H gloves. EVAL-Laminate gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Aerosol, Liquid
Color:	Gray, to, Off white
Odor:	Sharp, Solvent
Odor threshold:	Not available
pH:	Not available
Vapor pressure:	Not available
Boiling point/range:	Not available
Melting point/ range:	Not available
Specific gravity:	0.789
Vapor density:	Not available
Flash point:	< 5 °C (< 41°F)
Flammable/Explosive limits - lower:	Not available
Flammable/Explosive limits - upper:	Not available
Autoignition temperature:	Not available
Evaporation rate:	Not available
Solubility in water:	Slight
Partition coefficient (n-octanol/water):	Not available
VOC content:	30 %; 237 g/l

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Hydrochloric acid. Oxides of carbon. Irritating organic vapours.
Incompatible materials:	Acids and bases. Oxidizing agents. Sodium. Potassium.
Conditions to avoid:	Keep away from heat, spark and flame.

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Methylene chloride	Anticipated carcinogen.	Group 2B	Yes
Petroleum gases, liquified, sweetened	No	No	No
Methanol	No	No	No
Propylene oxide	Anticipated carcinogen.	Group 2B	No

Hazardous components	Health Effects/Target Organs
Methylene chloride	Blood, Cardiac, Central nervous system, Corrosive, Irritant, Kidney, Liver, Some evidence of carcinogenicity
Petroleum gases, liquified, sweetened	No Records
Methanol	Eyes, Heart, Irritant, Kidney, Liver, Metabolic, Nervous System, Reproductive
Propylene oxide	Corrosive, Irritant, Mutagen, Nervous System, Some evidence of carcinogenicity

12. ECOLOGICAL INFORMATION

Ecological information: Do not empty into drains / surface water / ground water.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Not available

Hazardous waste number: D001: Ignitable. U080: Methylene Chloride.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Aerosols
Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None
DOT Reportable quantity: Dichloromethane, Propylene oxide

International Air Transportation (ICAO/IATA)

Proper shipping name: Aerosols, flammable, containing substances in Division 6.1, Packing Group III
Hazard class or division: 2.1 (6.1)
Identification number: UN 1950
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: AEROSOLS (Methylene chloride)
Hazard class or division: 2.1 (6.1)
Identification number: UN 1950
Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12(b) Export Notification: None above reporting de minimus
CERCLA/SARA Section 302 EHS: Propylene oxide (CAS# 75-56-9).
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health, Fire, Sudden Release

CERCLA/SARA 313:

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Methanol (CAS# 67-56-1). Methylene chloride (CAS# 75-09-2). Propylene oxide (CAS# 75-56-9).

California Proposition 65:

This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDL Status:

All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

WHMIS hazard class:

A, B.1, D.1.B, D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: Lou Fabrizio, Regulatory Affairs Specialist For Safety and Regulatory information contact: Regulatory Affairs Rocky Hill, CT 860-571-5204

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.